

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) No. 305/2011



No. Intumastic HP – 20170519

- 1. Unique identification code of the product-type:** Intumastic HP
- 2. Intended use/es:** An acrylic based graphite sealant used to reinstate the fire resistance performance of wall and floor constructions where they have been provided with apertures for the penetration of single or multiple services.
- 3. Manufacturer:** tremco illbruck Limited, Coupland Road, Hindley Green, Wigan, UK, WN2 4HT
- 5. System/s of AVCP:** System 1
- 6. European Assessment Document:** ETAG 026 edition 2011 part 2
European Technical Assessment: ETA 17/0413
Technical Assessment Body: CPR Notified Body UL International UK Ltd, No. 0843
Notified body/ies: CPR Notified Body UL International UK Ltd, No. 0843
- 7. Declared performance/s**

Basic Work Requirement	Performance
Mechanical resistance and stability	
None	Not relevant
Safety in case of fire	
Reaction to fire (EN 13501-1)	Class E
Resistance to fire (EN 13501-2)	See ETA 17/0413 Annex A
Hygiene, Health and the Environment	
Air Permeability (EN 1026:2000)	NPD
Water Permeability (ETAG 026-2 Annex C)	NPD
Release of dangerous substances	Declaration of manufacturer – Use categories: IA3, S/W3
Safety in Use	
Mechanical Resistance and stability (EOTA TR001:2003)	NPD
Resistance to Impact / movement (EOTA TR001:2003)	NPD
Adhesion (EOTA TR001:2003)	NPD
Protection against noise	
Airborne Sound Insulation (EN10140-2 / EN ISO 717-1)	NPD
Energy, Economy and Heat Retention	
Thermal Properties (EN 12664, EN 12667 or EN 12939)	NPD
Water vapour permeability (EN ISO 12572 / EN 12086)	NPD
General Aspects Relating to fitness for use	
Durability and Serviceability (EN 13162 or EN 14303, EN ISO 1519)	Z ₁

NPD = No Performance Determined

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) No. 305/2011



8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Liptrot, Business Unit Leader Sealants and Coatings

A handwritten signature in blue ink, appearing to read "M. Liptrot", written over a light blue horizontal line.

At Wigan on 24th June 2019

Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) No. 305/2011



CE	
Firetherm Intumescent & Insulation Supplies Limited Unit F, Acorn Industrial Park Crayford Road Crayford Kent DA1 4FT 17 0843-CPR-0378 Intumastic HP – 20170519 www.firetherm.com/intumastichp/	
EN 1366-3: 2009 ETA 17/0413 ETAG 026, Part 2 An acrylic based graphite sealant used to reinstate the fire resistance performance of wall and floor constructions where they have been provided with apertures for the penetration of single or multiple services.	
Essential Characteristic	Performance
Safety in Case of Fire	
Reaction to fire	Class E
Resistance to fire	See ETA 17/0413 Annex A
Hygiene, Health and Environment	
Air Permeability	NPD
Water Permeability	NPD
Dangerous Substances	Declaration of manufacturer – Use categories: IA3, S/W3
Safety in use	
Mechanical resistance and stability	NPD
Resistance to impact/movement	NPD
Adhesion	NPD
Protection against noise	
Airborne sound insulation	NPD
Energy, Economy and Heat Retention	
Thermal properties	NPD
Water vapour permeability	NPD
General aspects relating to fitness for use	
Service & Durability	Z ₁