

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) No. 305/2011



**No. Intusil - 20170905**

- 1. Unique identification code of the product-type:** Intusil
- 2. Intended use/es:** A fire resistant, one part silicone based sealant used to form linear gap seals where gaps are present in wall and floor constructions.
- 3. Manufacturer:** Firetherm Intumescent and Insulation Supplies Limited, Unit F Acorn Industrial Park, Crayford Road, Crayford, Kent, DA1 4FT
- 5. System/s of AVCP:** System 1
- 6. European Assessment Document:** ETAG 026 edition 2011 used as EAD  
**European Technical Assessment:** ETA 17/0717  
**Technical Assessment Body:** Warrington Certification Limited  
**Notified body/ies:** 1121, Warrington Certification Limited
- 7. Declared performance/s**

Essential Characteristic	Performance	Harmonised Technical Specification
<b>Safety in Case of Fire</b>		
Reaction to fire	Class F	EN13501-1
Resistance to fire	Up to EI240 Resistance to fire performance, in accordance with EN13501-2 See ETA 17/0717 clause 3.2 – Annex C	EN 13501-2
<b>Hygiene, Health and the Environment</b>		
Dangerous Substances	Does not contain dangerous substances See ETA 17/0717 Clause 3.5	
Air Permeability	Test Pressure Differential 600Pa See ETA 17/0717 Clause 3.4	EN 1026
<b>Energy, Economy and Heat Retention</b>		
Service and Durability	X intended for use in conditions exposed to weathering in accordance with EOTA Technical Report TR024 – Edition Nov 2006	ETAG 026-3

NPD = No Performance Determined

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) No. 305/2011



## 8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Signed for and on behalf of the manufacturer by:

*M. Liptrot, Business Unit Leader Sealants and Coatings*

A handwritten signature in blue ink, appearing to read "M. Liptrot", written over a light blue horizontal line.

*At Wigan on 9 October 2017*

## Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) No. 305/2011



<b>CE</b>	
Firetherm Intumescent & Insulation Supplies Limited Unit F, Acorn Industrial Park Crayford Road Crayford Kent DA1 4FT 17 1121-CPR-JA5110 Intusil – 20170905 <a href="http://www.firetherm.com/intusil/">www.firetherm.com/intusil/</a>	
EN 1366 Part 4 ETA 17/0717 ETAG 26, Part 3 A fire resistant, one part silicone based sealant used to form linear gap seals where gaps are present in wall and floor constructions.	
<b>Essential Characteristic</b>	<b>Performance</b>
<b>Safety in Case of Fire</b>	
Reaction to fire	Class F
Resistance to fire	Up to EI240 resistance to fire performance, in accordance with EN13501-2 See ETA 17/0717 clause 3.2 – Annex C
<b>Hygiene, Health and Environment</b>	
Air Permeability	Test pressure differential 600Pa See ETA 17/0717 clause 3.4
Dangerous Substances	Does not contain dangerous substances See ETA 17/0717 clause 3.5
<b>Energy, Economy and Heat Retention</b>	
Service & Durability	X intended for use in conditions exposed to weathering in accordance with EOTA Technical report TR024 – Edition Nov 2006