

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) No. 305/2011



No. Intubatt - 20170519

- 1. Unique identification code of the product-type:** Intubatt
- 2. Intended use/es:** A mineral wool board coated on both faces used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.
- 3. Manufacturer:** Firetherm Intumescent and Insulation Supplies Limited, Unit F Acorn Industrial Park, Crayford Road, Crayford, Kent, DA1 4FT
- 5. System/s of AVCP:** System 1
- 6. European Assessment Document:** ETAG 026 edition 2011 part 2
European Technical Assessment: ETA 16/0106
Technical Assessment Body: CPR Notified Body UL International UK Ltd, No. 0843
Notified body/ies: CPR Notified Body UL International UK Ltd, No. 0843
- 7. Declared performance/s**

Basic Work Requirement	Performance
Mechanical resistance and stability	
None	Not relevant
Safety in case of fire	
Reaction to fire (EN 13501-1)	Class E
Resistance to fire (EN 13501-2)	See ETA16/0106 Annex A
Hygiene, Health and the Environment	
Air Permeability (EN 1026:2000)	See ETA16/0106 Annex B
Water Permeability (ETAG 026-2 Annex C)	NPD
Release of dangerous substances	Declaration of manufacturer – Use categories: IA3, S/W3
Safety in Use	
Mechanical Resistance and stability (EOTA TR001:2003)	NPD
Resistance to Impact / movement (EOTA TR001:2003)	NPD
Adhesion (EOTA TR001:2003)	NPD
Protection against noise	
Airborne Sound Insulation (EN10140-2 / EN ISO 717-1)	See ETA16/0106 Annex C
Energy, Economy and Heat Retention	
Thermal Properties (EN 12664, EN 12667 or EN 12939)	NPD
Water vapour permeability (EN ISO 12572 / EN 12086)	NPD
General Aspects Relating to fitness for use	
Durability and Serviceability (EOTA TR 024:2009)	Z ₁

NPD = No Performance Determined

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) No. 305/2011



8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Signed for and on behalf of the manufacturer by:

M. Liptrot, Business Unit Leader Sealants and Coatings

A handwritten signature in blue ink, appearing to read "M. Liptrot".

At Wigan on 9 October 2017

Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) No. 305/2011



CE	
Firetherm Intumescent & Insulation Supplies Limited Unit F, Acorn Industrial Park Crayford Road Crayford Kent DA1 4FT 17 0843-CPR-0368 Intubatt – 20170519 www.firetherm.com/intubatt	
EN 1366 Part 3 ETA 16/0106 ETAG 26, Part 2	
A mineral wool board coated on both faces used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.	
Essential Characteristic	Performance
Safety in Case of Fire	
Reaction to fire	Class E
Resistance to fire	ETA 16/0106 Annex A
Hygiene, Health and Environment	
Air Permeability	ETA 16/0106 Annex B
Water Permeability	NPD
Dangerous Substances	Declaration of manufacturer – Use categories: IA3, S/W3
Safety in use	
Mechanical resistance and stability	NPD
Resistance to impact/movement	NPD
Adhesion	NPD
Protection against noise	
Airborne sound insulation	ETA 16/0106 Annex C
Energy, Economy and Heat Retention	
Thermal properties	NPD
Water vapour permeability	NPD
General aspects relating to fitness for use	
Service & Durability	Z ₁